

# SELPHY QX20

COMPACT PHOTO PRINTER

---

## TECHNICAL SPECIFICATIONS



**Canon**

# SELPHY QX20

## COMPACT PHOTO PRINTER

Bring colour to your everyday



### TWO PAPER SIZES IN ONE PRINTER

Simply change the paper to choose between card-size and square format. Expand the creative possibilities with bordered and borderless for each.



### CLEARER AND MORE VIVID

Print images from your phone faithfully as you imagined them, with smooth gradations, beautiful color reproduction for skin tones, and vivid colors.



### BEAUTY THAT LASTS 100-YEARS

A special protective overcoat is applied to cover the photo after the printing process. This protects your important prints against water and dirt and prevents color bleeding and fading.



### EASY CONNECTION TO YOUR SMARTPHONE

Simply download the free SELPHY Photo Layout 4.0 app, connect your phone to your printer via Wi-Fi and follow the instructions. Alternatively, scanning the QR code on the printer itself will easily connect your printer to your smartphone.



**Canon**

# SELPHY QX20 | SPECIFICATIONS

## COMPACT PHOTO PRINTER

PRINTER FUNCTIONS	
Printing method	Dye-sublimation thermal transfer
Album storage	100 years supported
Print resolution	287 x 287 dpi
Gradation	256 shades per colour
Printer speed* <sup>1</sup>	Approx. 40 sec.
Number of printable sheets* <sup>2</sup>	Approx. 20 sheets
Paper feed capacity	10 sheets
DIMENSIONS AND WEIGHT	
Dimensions (WxHxD)* <sup>3</sup>	Approx. 102.2 x 32.9 x 145.8 mm
Weight* <sup>4</sup>	Approx. 455g
POWER SOURCE	
Printing while charging	Not supported
Battery Type	Built-in Lithium-ion battery
Nominal voltage (DC)	7.4 V
Nominal capacity	850 mAh
Battery rated input (voltage)	DC 0.5 V ± 0.5 V
Battery rated input (current)	Max 1.5A
Charging time* <sup>5</sup>	Approx. 1 hr 20 min
Charging cable terminal	USB Type-C
EXTERNAL INTERFACE	
Wi-Fi spec & frequency	2.4GHz. IEEE802.11 b/g compliant.
Wi-Fi security	WPA3-Personal Transition Mode
Connection method	Direct connection – SELPHY Photo Layout app 4.0 or later
Simultaneous connections	6 devices
Other	Memory card – not supported Communication via USB cable – not supported
Consumables	XS-20L, XC-20L, XC-60L

## VARIATIONS



BLACK

RED

WHITE

\*1 Measurement conditions: Room temperature (23°C/73°F), from start of printing until paper ejection is finished.

\*2 Measurement conditions: Room temperature (23°C/73°F), using a new, fully charged battery, based on Canon testing standards.

\*3 Excluding the projecting parts

\*4 Excluding the colour ink cassette and labels

\*5 At room temperature. May take approx. 4 hours if the battery is fully discharged, such as when initially charged or after extended storage.

**Canon**

**[www.canon.com.au](http://www.canon.com.au)  
[www.canon.co.nz](http://www.canon.co.nz)**