

Part No. 36923

3m DisplayPort to HDMI 10.2G Cable

CONNECT DISPLAYPORT DEVICES TO AN HDMI DISPLAY



DESCRIPTION

RELATED PRODUCTS

- Connects a DisplayPort equipped device to a 4K UHD HDMI display or projector
- Supports resolutions up to 3840x2160@30Hz
- ${\boldsymbol{\cdot}}$ Supports video mirroring and extended desktop modes
- ${\boldsymbol{\cdot}}$ Audio pass-through if supported by the video source
- 2 year warranty

The Lindy DisplayPort to HDMI Cable is ideal for connecting a DisplayPort equipped source such as a PC or laptop to an HDMI display. Supporting 4K UHD resolutions up to 3840x2160@30Hz, this cable is ideal for ensuring video is displayed in superior clarity. This cable can also be used to add another display to extend the available desktop workspace and increase productivity, great for use in residential or workplace office setups.

The DisplayPort to HDMI Cable supports uncompressed 7.1 Audio and compressed Audio such as DTS-HD Master Audio, Dolby TrueHD. Please note that audio output over HDMI is only supported when the graphics card of the laptop or desktop computer supports audio output over DisplayPort.

0

3m DisplayPort to HDMI 10.2G Cable



CONNECTORS

DisplayPort Male **Connector A HDMI Type A Male Connector B**

DisplayPort: ABSHDMI: PVC **Housing Material**

Connector Plating Gold plated Copper **Pin Construction** Gold plated Pin Plating

Dimensions (approx.) WxDxH DisplayPort:36.4x20.5x9.4m

m (1.43x0.81x0.37in) HDMI: 37.5x20.5x10.5mm (1.48x0.81x0.41in)

CABLE CONSTRUCTION

Length 3m (9.84ft) **HDMI 1.4** Standard

DisplayPort 1.2

Colour Black Round Туре

7.3mm (0.29in) Jacket Diameter

Jacket Material PVC

Conductor Material **Tinned Copper** Conductor Gauge 28AWG

Shielding Aluminium Braid 85%

SPECIFICATONS

10.2Gbps Supported Bandwidth

3840x2160@30Hz 4:4:4 8bit Maximum Resolution

100MHz-450MHz 2.44-Nominal Attenuation

5.099dB

450MHz-8100MHz 5.094-

32.906dB

Minimum Bend Radius 73mm (2.87in)

0°C - 45°C (32°F - 113°F) Operating Temperature -10°C - 80°C (14°F - 176°F) Storage Temperature

MISCELLANEOUS

Packaging Type Polybag Warranty (Years)

Certificated

CE, FCC, RoHS, REACH, UL & California Proposition 65

PURCHASING INFORMATION

36923 No.

EAN 4002888369237

AVAILABLE IN OTHER LENGTHS

36920 - 0.5m (1.64ft) 36921 - 1m (3.28ft) 36922 - 2m (6.56ft) 36923 - 3m (9.84ft) 36924 - 5m (16.44ft)