

Part No. 36922

# 2m DisplayPort to HDMI 10.2G Cable

CONNECT DISPLAYPORT DEVICES TO AN HDMI DISPLAY



#### DESCRIPTION

- Connects a DisplayPort equipped device to a 4K UHD HDMI display or projector
- Supports resolutions up to 3840x2160@30Hz
- $\boldsymbol{\cdot}$  Supports video mirroring and extended desktop modes
- Audio pass-through if supported by the video source
- 2 year warranty

The Lindy DisplayPort to HDMI Cable is ideal for connecting a DisplayPort equipped source such as a PC or laptop to an HDMI display. Supporting 4K UHD resolutions up to 3840x2160@30Hz, this cable is ideal for ensuring video is displayed in superior clarity. This cable can also be used to add another display to extend the available desktop workspace and increase productivity, great for use in residential or workplace office setups.

The DisplayPort to HDMI Cable supports uncompressed 7.1 Audio and compressed Audio such as DTS-HD Master Audio, Dolby TrueHD. Please note that audio output over HDMI is only supported when the graphics card of the laptop or desktop computer supports audio output over DisplayPort.

0

RELATED PRODUCTS

# 2m DisplayPort to HDMI 10.2G Cable

### CONNECTORS

Connector A Connector B Housing Material Connector Plating Pin Construction Pin Plating Dimensions (approx.) WxDxH DisplayPort Male HDMI Type A Male DisplayPort: ABSHDMI: PVC Gold plated Copper Gold plated DisplayPort:36.4x20.5x9.4m m (1.43x0.81x0.37in) HDMI: 37.5x20.5x10.5mm (1.48x0.81x0.41in)

# CABLE CONSTRUCTION

Length	2m (6.56ft)
Standard	HDMI 1.4
	DisplayPort 1.2
Colour	Black
Туре	Round
Jacket Diameter	7.3mm (0.29in)
Jacket Material	PVC
Conductor Material	Tinned Copper
Conductor Gauge	28AWG
Shielding	Aluminium Braid 85%

#### SPECIFICATONS

Supported Bandwidth Maximum Resolution 10.2Gbps 3840x2160@30Hz 4:4:4 8bit

Nominal Attenuation

Minimum Bend Radius Operating Temperature Storage Temperature 100MHz-450MHz 2.44-5.099dB 450MHz-8100MHz 5.094-32.906dB 73mm (2.87in)

0°C - 45°C (32°F - 113°F) -10°C - 80°C (14°F - 176°F)

#### MISCELLANEOUS

Packaging Type Warranty (Years) Certificated Polybag 2 CE, FCC, RoHS, REACH, UL & California Proposition 65

#### PURCHASING INFORMATION

No. EAN 36922 4002888369220

## AVAILABLE IN OTHER LENGTHS

36920 - 0.5m (1.64ft) 36921 - 1m (3.28ft) 36922 - 2m (6.56ft) 36923 - 3m (9.84ft) 36924 - 5m (16.44ft)

